



# CRA GRADE 30 SHORT LINK ANCHOR CHAIN RANGE

## DIN766/A G30 SHORT LINK

| Article code | Manufacturer | Diameter (d) | Inner pitch (p) | Maximum width (H) | Weight | Working load | Breaking load |
|--------------|--------------|--------------|-----------------|-------------------|--------|--------------|---------------|
|              |              | mm           | mm              | mm                | kg/mt  | kN           | kN            |
| CHS006MFG3   | MFI Italy    | 6            | 18,5            | 20.4              | 0.8    | 4            | 16            |
| CHS006RD     | RCW China    | 6            | 18,5            | 19.8              | 0.76   | 3.8          | 16            |
| CHS007MFG3   | MFI Italy    | 7            | 22              | 23.8              | 1,10   | 6.3          | 25            |
| CHS007RD     | RCW China    | 7            | 22              | 23.2              | 1.05   | 6.18         | 25            |
| CHS008MFG3   | MFI Italy    | 8            | 24              | 27.2              | 1.4    | 8            | 32            |
| CHS008RD     | RCW China    | 8            | 24              | 26.7              | 1.36   | 7.8          | 32            |
| CHS008MFG3   | MFI Italy    | 10           | 28              | 36                | 2.3    | 12.5         | 50            |
| CHS01028RD   | RCW China    | 10           | 28              | 35.1              | 2.25   | 12.2         | 50            |
| CHS013MFG3D  | MFI Italy    | 13           | 36              | 47                | 3.9    | 20           | 80            |
| CHS014MFG3D  | MFI Italy    | 14           | 41              | 50                | 4.4    | 25           | 100           |
| CHS016MFG3D  | MFI Italy    | 16           | 45              | 58                | 5.8    | 32           | 125           |

## CHAINS ROPES & ANCHORS T ISO4565 G30 SHORT LINK\*

| Article code | Manufacturer | Diameter (d) | Inner pitch (p) | Maximum width (H) | Weight | Working load | Breaking load |
|--------------|--------------|--------------|-----------------|-------------------|--------|--------------|---------------|
|              |              | mm           | mm              | mm                | kg/mt  | kN           | kN            |
| CHS012MFG3S  | MFI Italy    | 12           | 36              | 43.2              | 2.7    | 17.75        | 71            |

\* - The ISO4565 Standard is a Grade 40 standard but Italy builds us a G30 version. This has the same physical dimensions as the ISO Std requires but with lower loads.

## NF E 26-011L G30 SHORT LINK

| Article code  | Manufacturer | Diameter (d) | Inner pitch (p) | Maximum width (H) | Weight | Working load | Breaking load |
|---------------|--------------|--------------|-----------------|-------------------|--------|--------------|---------------|
|               |              | mm           | mm              | mm                | kg/mt  | kN           | kN            |
| CHS014MFG4SSZ | MFI Italy    | 14           | 42              | 47.6              | 4.25   | 25           | 100           |
| CHS016MFG4SSZ | MFI Italy    | 16           | 48              | 54.4              | 5.8    | 32           | 128           |