



GRADE 40 SHORT LINK ANCHOR CHAIN RANGE

DIN766/A G40 SHORT LINK#

| Article code | Manufacturer | Finish | Diameter (d) | Inner pitch (p) | Maximum width (H) | Weight | Working load | Breaking load |
|----------------|--------------|---------------|--------------|-----------------|-------------------|--------|--------------|---------------|
| | | | mm | mm | mm | kg/mt | kN | kN |
| CHS006MFG4SZ~ | MFI Italy | Solid Zinc | 6 | 18,5 | 20.4 | 0.8 | 5 | 22 |
| CHS006RGG4 | Riga Italy | Hot Dip Galv | 6 | 18,5 | 20.4 | 0.81 | 5 | 22 |
| CHS007MFG4SZ | MFI Italy | Solid Zinc | 7 | 22 | 23.8 | 1,10 | 8 | 31 |
| CHS007RGG4 | Riga Italy | Hot Dip Galv | 7 | 22 | 23.2 | 1.07 | 8 | 31 |
| CHS008MFG4DSZ | MFI Italy | Solid Zinc | 8 | 24 | 27.2 | 1.4 | 10 | 40 |
| CHS008RGG4 | Riga Italy | Hot Dip Galv | 8 | 24 | 27.1 | 1.41 | 10 | 40 |
| CHS010MFG4DSZ | MFI Italy | Solid Zinc | 10 | 28 | 36 | 2.3 | 16 | 63 |
| CHS010RGG4D | Riga Italy | Hot Dip Galv | 10 | 28 | 37 | 2.25 | 15 | 62 |
| CHS013MFG4DSZ | MFI Italy | Solid Zinc | 13 | 36 | 47 | 3.9 | 26 | 106 |
| CHS014MFG4SSZ | MFI Italy | Hot Dip Galv* | 14 | 41 | 50 | 4.4 | 31 | 123 |
| CHS016MFG4DSZ | MFI Italy | Hot Dip Galv* | 16 | 45 | 58 | 5.8 | 40 | 161 |
| CHS018MFG4DSZ~ | MFI Italy | Hot Dip Galv* | 18 | 50 | 65 | 7.4 | 51 | 203 |
| CHS020MFG4DSZ~ | MFI Italy | Hot Dip Galv* | 20 | 56 | 72 | 9 | 63 | 251 |

CHAINS ROPES & ANCHORS
THE EXPERTS IN SPECIALISTS

ISO4565 G40 SHORT LINK

| Article code | Manufacturer | Finish | Diameter (d) | Inner pitch (p) | Maximum width (H) | Weight | Working load | Breaking load |
|---------------|--------------|--------------|--------------|-----------------|-------------------|--------|--------------|---------------|
| | | | mm | mm | mm | kg/mt | kN | kN |
| CHS010MFG4SSZ | MFI Italy | Solid Zinc | 10 | 30 | 37 | 2.3 | 16 | 63 |
| CHS010RGG4S | Riga Italy | Hot Dip Galv | 10 | 30 | 37 | 2.25 | 15 | 62 |
| CHS012MFG4SSZ | MFI Italy | Solid Zinc | 12 | 36 | 43.2 | 3.12 | 22 | 90 |

NF E 26-011M G40 SHORT LINK

| Article code | Manufacturer | Finish | Diameter (d) | Inner pitch (p) | Maximum width (H) | Weight | Working load | Breaking load |
|---------------|--------------|---------------|--------------|-----------------|-------------------|--------|--------------|---------------|
| | | | mm | mm | mm | kg/mt | kN | kN |
| CHS014MFG4SSZ | MFI Italy | Hot Dip Galv* | 14 | 42 | 47.6 | 4.25 | 25 | 100 |
| CHS016MFG4SSZ | MFI Italy | Hot Dip Galv* | 16 | 48 | 54.4 | 54.4 | 32 | 128 |

Notes:
 # - The DIN766/A Standard is a G30 but our Italian mates build us a G40 version. Same dimentions just stronger than the standard requires.
 * - coming shortly in Solid Zinc finish
 ~ - Non-stock at this stage but available by special order
 Specifications subject to change by ISO and/or the manufacturer (unlikely though)
 Commercial tolerances are in play
 Some terminology is regional and/or simplified